

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number
WO 2005/076394 A2

(51) International Patent Classification⁷: **H01M 8/00**, 8/24

KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

(21) International Application Number:

PCT/JP2005/001973

(74) Agent: **ITEC INTERNATIONAL PATENT FIRM**; Pola-Nagoya Bldg., 9-26, Sakae 2-chome, Naka-ku, Nagoya-shi, Aichi 4600008 (JP).

(22) International Filing Date: 2 February 2005 (02.02.2005)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

English

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(26) Publication Language: English

(30) Priority Data:

2004-029771 5 February 2004 (05.02.2004) JP
2004-349942 2 December 2004 (02.12.2004) JP

(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **SUZUKI, Hiroshi** [JP/JP]; c/o **TOYOTA JIDOSHA KABUSHIKI KAISHA**, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **YODOSHI, Nobuo** [JP/JP]; c/o **TOYOTA JIDOSHA KABUSHIKI KAISHA**, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **TEJIMA, Go** [JP/JP]; c/o **TOYOTA JIDOSHA KABUSHIKI KAISHA**, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **NAKASHIMA, Tomoaki** [JP/JP]; c/o **TOYOTA JIDOSHA KABUSHIKI KAISHA**, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **AKAGAWA, Ryo** [JP/JP]; c/o **TOYOTA JIDOSHA**

Published:

- without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: FUEL CELL DISASSEMBLY METHOD



(57) **Abstract:** Respective heaters 21 through 24 receive power supply and start heating. The heaters 21 through 24 keep heating sealing layers 8 to or over a softening temperature at which the sealing layers 8 are softened or molten. After the sealing layers 8 are softened or molten to weaken the adhesive force between a pair of separators 6 and 7, the heaters 21 through 24 are detached from a fuel cell 10. The worker then completely separates the pair of separators 6 and 7 from each other with some tool or by hand and removes an MEA 2 from the fuel cell 10.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.